

Lab1st DC series heating cooling circulator is an open table type circulator with compact structure and small footprint. Its temperature range is -5C - 95C.



Table-top Heating Cooling Bath Circulator

Features:

- Realize inside and outside circulation, achieve "constant temperature" in the liquid tank
- The compressor can be started at high temperature
- Intelligent control system, rapid temperature rise, stable temperature, easy to operate
- Benchtop design, compact structure
- Open bath, suitable for internal/external applications
- Suitable for small applications with high precision

Technical Data:

Model	DC-10-06L
Technical Data	
Temp. Range	-10~95°C; ±0.05°C
Environment Temp. Range	5~30°C
Optimum Ambient Humidity	45~80% RH
Electrical Requirements	220V; 1P; 50/60HZ
Heating Power [W]	800
Temp. Sensor	PT100
Safety	Multiple protection of overheat and overcurrent
Certification	CE
Compressor	
Power [W]	130
Refrigerating Fluid	R134A
Fluid Bath	
Bath Dimension [mm]	280×220×120
Bath Openings Size [mm]	180×140
Circulation Interface	10mm Barb×2

Drain Connection	8mm
Circulation Pump	
Lift [m]	1
Rated Flow [L/min]	6
Weight Dimension	
Running Weight [Kg]	22
Unit Dimension [mm]	370×320×650

Package Information:

Length (cm)	Width (cm)
Height (cm)	CBM (m3)
Weight (kg)	Total capacity
Product Serial No. 9013	2024-02-05 15:18:23

Technical details and dimensions are subject to change. No liability is accepted for errors or omissions. Illustrations can deviate from the original.



Lab1st DC series heating cooling circulator is an open table type circulator with compact structure and small footprint. Its temperature range is -10C to 95C.



Table-top Heating Cooling Bath Circulator

Features:

- Realize inside and outside circulation, achieve "constant temperature" in the liquid tank
- The compressor can be started at high temperature
- Intelligent control system, rapid temperature rise, stable temperature, easy to operate
- Benchtop design, compact structure
- Open bath, suitable for internal/external applications
- Suitable for small applications with high precision

Technical Data:

Model	DC-10-10L
Technical Data	
Temp. Range	-10~95°C; ±0.05°C
Environment Temp. Range	5~30°C
Optimum Ambient Humidity	45~80% RH
Electrical Requirements	220V; 1P; 50/60HZ
Heating Power [W]	800
Temp. Sensor	PT100
Safety	Multiple protection of overheat and overcurrent
Certification	CE
Compressor	
Power [W]	130
Refrigerating Fluid	R134A
Fluid Bath	
Bath Dimension [mm]	280×220×165
Bath Openings Size [mm]	180×140
Circulation Interface	10mm Barb×2

Drain Connection	8mm
Circulation Pump	
Lift [m]	8
Rated Flow [L/min]	10
Weight Dimension	
Running Weight [Kg]	26
Unit Dimension [mm]	400×350×820

Package Information:

Length (cm)	Width (cm)
Height (cm)	CBM (m3)
Weight (kg)	Total capacity
Product Serial No. 9013	2024-02-05 15:19:00

Technical details and dimensions are subject to change. No liability is accepted for errors or omissions. Illustrations can deviate from the original.

