

BR500-M1-100L Microbial Fermentation System Technical Specifications

Prepared by Labfirst Scientific, October 2023 Email: sales@lab1st.com; Tel: +86-13524020331



1. General Information

Items Included	Control Console	BR500-M1
	6 th	100L tank SUS316L, 3 layers, with top mechanical stirring
	Culture Vessel	(25~70% working volume)
	Sensors	PT100, DO, foam, pH
	Feeding Pumps	4 PreFluid peristaltic pump heads, controlled
		· Sparger from the bottom (Air +O2);
	Gas Inlet	· Air inlet controlled by rotameter (manually);
		O2 inlet controlled by rotameter and electromagnetic valve
	Heating & Cooling	The jacketed water bath is electrically heated, chilled by chilled water supply;
	Accessories	4 supplement bottles, SS316L feeding needle, etc.
	Consumables	O-rings, fuses, silicone stoppers, inlet air filter, vent filter, 20m silicone tubing, etc.
Sensors Included	рН	Gel-filled pH electrode by Hamilton / Mettler Brand (steam sterilizable), with 3m cable
	DO	Sterilizable probe by Hamilton / Mettler Brand, with 3m cable
	Temperature	PT100 sensor, sterilizable
	Foam	Foam probe, sterilizable
	Pressure	Huba pressure sensor, sterilizable, Swiss Brand



2. Specific Information

		· Robust PID algorithm;
Functions Included	Temperature	The jacketed water bath is electrically heated, chilled by
		chilled water supply;
		· Sequential control coupled with fermentation process
	рH	· pH control coupled with peristaltic pump;
		· Manual pH control by peristaltic pump
	DO	· Cascade control, coupled with different parameters
		(agitation, gas inlet and peristaltic pump)
	Agitation	· Robust PID algorithm;
		· Manual speed control or speed control coupled with other
		parameters;
		· Agitation speed control coupled with other parameters (like
		DO)
	Foam	· Foam control coupled with peristaltic pump; (anti-foam);
		· Mechanical defoaming blade;
	Automatic SIP	SIP with pre-set automatic sequence
	Feeding (peristaltic pump)	· Accumulation volume control;
		· Manual control or control by plan (pre-set) curve;
		· Coupled with other parameters (DO, pH, etc)
	Fermentation	Pre-set fermentation sequences along with timeline (pH, DO,
	Sequence	agitation, temperature, etc)
	Others	· Historical data export and curves;
		· Fermentation/culture batch record;
		· Calibration of sensors and peristaltic pumps;
		· 3-level authority setting & control;
		· Record historical operations

2. 1 Control Console

General Info	Model	BR500-M1
	Description	Floor stand control console for microbial fermentation, 1
	Description	console for 1 vessel
	Dimension	650×650×1492mm
	Net Weight	110 Kg
	Touch Screen	PLC based 15" touch screen
	Communication	USB (data export), Ethernet interface, RS485
	Electricity	208V-240V, single phase / 353V-406V, 3 phase; 50-60Hz
		· Sparger from the bottom (Air +O2);
Gas Inlet	Control	· Air inlet controlled by rotameter (manually);
		· O2 inlet controlled by rotameter and electromagnetic valve
	Flow Rate	2 vvm
	Filtration	0.2 um
	Connection	Pneumatic quick joint



Temperature	Range	8C above coolant to 40C above ambient (0-65C absolute)
	Control Accuracy	+/- 0.1C
рН	Range	2.00~12.00 (resolution 0.01)
	Control Accuracy	+/- 0.1
DO	Range	0~150% (resolution 0.1%)
	Control Accuracy	+/- 3%
Unarados	Analysis or Control	OUR, CER, KLa, RQ,ORP, methanol, exhaust gas (O2, CO2),
Upgrades		glucose, ect.
	Pressure Control	Automatically control pressure
	Automatic CIP	CIP with pre-set automatic sequence
	Gas Inlet	Up to 4 channels (O2, CO2, N2 & air)
	Gas Supply Control	TMFC control (flow rate - automatic)
	Peristaltic Pump	More peristaltic pumps for different function;
		Upgrade to Watson-Marlow peristaltic pump heads;
	Scale	Tank weight / replenishing
	Light	Light source can be selected from red, blue, and white. Its
		intensity is adjustable [0-100%]
		intensity is adjustable [0-100%]

2.2 Vessel Information

General Info	Volume	100L max, with 25-70% working volume
	Material	3 layers, tank SUS316L (polishing better than Ra 0.4 um),
	iviaterial	jacket SUS304, insulation SUS304 (aluminum silicate filled)
	Ratio	Diameter to height, about 1:2
	Rated Pressure	0.30 Mpa
		Lid: 1 x fire ring, 1 x foam sensor, 1 x exhaust with condenser,
	Ports	2 x spray header ports, 1 × illumination, 2 x spares; Body: 1 x
		pH, 1 x DO, 1 x PT100, 1 x vertical sight glass, 1 x spare
	Sterilization	Autoclavable
	Sparge	SS316L ring sparger in the bottom
	Dimension	1000×2600×1000mm
	Net Weight	360Kg
	Seal	Top mechanical stirring
	Speed	50 - 1000 rpm
		4 detachable layers (ten: 1 y feam breaker; bettem: 2 y 6
Agitation	Blades	4 detachable layers (top: 1 x foam breaker; bottom: 2 x 6-
	- CC	blade rushton impeller, 1 x 4-blade pitched impeller)
	Baffles	4pcs
Upgrades	Drive	Top Magnetic drive
	Lid	Optional motor lift
		Customizable blades from different options (Spin filter, Cell-lift
	Blades	impeller, Basket impeller, Pitched Blade Impeller, Marine
		Blade Impeller)