

# M700 pH/Ion Meter



## pH

- 1-6 points calibration with Standard Recognition.
- Selectable pH buffer groups, including DIN, NIST, USA, MERK, JIS, GB.
- Support for pH standard group customization.
- Automatic electrode diagnosis with pH slope and offset display.

## GENERAL FEATURES

- Color High contrast LCD touchscreen, 7.0 inches.
- Intelligent operation system provides features including user management, calibration management, method management, data management and etc.
- Multi-reading feature allows auto-read, timed-read and continuous-read.
- Automatic/Manual temperature compensation ensures accurate results.
- Data Storage 1000 sets for each parameter (GLP-compliant).
- Data analysis feature helps user review, compare and recalculate results.
- Support for USB or RS-232 communication.
- Reset feature automatically resumes all settings back to factory default options.
- IP54 waterproof.

## Ion

- 1-6 points calibration
- Selectable measurement unit, including  $\mu\text{g/L}$ ,  $\text{mg/L}$ ,  $\text{g/L}$ ,  $\text{mmol/L}$ ,  $\text{pX}$ ,  $\text{ppm}$ ,  $\text{ppb}$ , etc.
- Multi-measurement modes are supported, including Direct Reading mode, Standard Addition mode, Sample Addition mode and GRAN mode.
- Over 10 methods are built-in, including  $\text{F}^-$ ,  $\text{Cl}^-$ ,  $\text{Br}^-$ ,  $\text{I}^-$ ,  $\text{NO}_3^-$ ,  $\text{BF}_4^-$ ,  $\text{NH}_4^+$ ,  $\text{K}^+$ ,  $\text{Na}^+$ ,  $\text{Ca}^{2+}$ ,  $\text{Cu}^{2+}$ ,  $\text{Pb}^{2+}$ ,  $\text{Ag}^+$  and etc., user-defined method is supported.

| Model           | M700                    |  |
|-----------------|-------------------------|--|
| Parameters      | pH/ISE/Temp.(mV/ORP/pX) |  |
| pH              | Range                   | -2.000 to 20.000 pH                                  |
|                 | Resolution              | 0.1, 0.01, 0.001pH                                   |
|                 | Accuracy                | $\pm 0.002$ pH                                       |
|                 | Calibration Points      | Up to 6  |
|                 | Standard Customization  | Yes  |
|                 | Calibration Reminder    | Yes  |
|                 | Standard Recognition    | NIST, GB, DIN, USA, MERK, JIS buffers                |
| mV/ORP          | Slope Limit             | Yes  |
|                 | Range                   | -2000.00 to 2000.00 mV                               |
|                 | Resolution              | 0.1, 0.01 mV   |
|                 | Accuracy                | reading whichever is greater                         |
|                 | EH ORP Mode             | Yes  |
| pX              | ORP Calibration Points  | 1 custom point (relative mV)                         |
|                 | Range                   | -2.000 to 20.000 pX                                  |
|                 | Resolution              | 0.1, 0.01, 0.001 pX                                  |
|                 | Accuracy                | $\pm 0.002$ pX                                       |
| ISE             | Calibration Points      | Up to 6  |
|                 | Range                   | 1.000e-9 to 9.999e+9                                 |
|                 | Units                   | mol/L, mmol/L, g/L, mg/L, $\mu\text{g/L}$ , ppm, ppb |
|                 | Resolution              | Up to 4 significant digits                           |
| Temperature     | Accuracy                | $\pm 0.3\%$  |
|                 | Calibration Points      | Up to 6  |
|                 | Range                   | -10 to 135 °C, 14 to 275 °F                          |
|                 | Unit                    | °C, °F   |
| Measurement     | Resolution              | 0.1  |
|                 | Accuracy                | $\pm 0.1$  |
|                 | Reading Mode            | Auto Read (Fast, Medium, Slow), Timed, Continuous    |
| Data management | Reading Prompts         | Reading, Stable, Locked                              |
|                 | Temp. Compensation      | ATC, MTC   |
|                 | Data Storage            | 1000 Groups  |
| Inputs          | GLP Features            | Yes  |
|                 | Log Management          | Yes  |
| Outputs         | pH Electrode            | BNC(Q9)  |
|                 | Temp. Probe             | 4-pin aviation connector                             |
| Display options | USB                     | USB 2.0 flash memory device, PC, scanner             |
|                 | RS 232                  | printer, auto-sampler                                |
| General         | Backlight               | Yes  |
|                 | Auto Shutdown           | 1~60 min, off  |
|                 | IP Rating               | IP54   |
| General         | Date and Time           | Yes  |
|                 | Power                   | AC Adapter, 100-240V AC input, DC24V output          |
|                 | Dimensions              | 220 × 195 × 68 mm                                    |
|                 | Weight                  | 950g (2.09 lb)                                       |