

RE-150

Rotary evaporator is a common solvent recvery equipment in laboratory and production for chemistry, chemical industry, biology, medicine and other fields.

Lab1st RE-1 series is a rotary evaporator with manual lifting bath, which is easy to operate, economical and practical. It also consists of motor, roatary flask, manual lifting bath, condenser and other related parts. We provide standard rotovap from 1 liter to 100 liters, and larger volumes can be customized.



Rotary Evaporator with Hand Lift (>=10L)

Features:

Effective Rotavapor for limited budgets

Intuitive and easy operation at the highest safety level

High quality material guarantees a long lasting operation and protect your substance

All material is corrosion resistance and long lifespan, maintaining vecuum height.

Powerful, high-temperature heating bath, reaching 90°C [water bath] / 180°C [oil bath]

Turnkey solution is available, including chiller, vacuum pump and related accessories

Technical Data:

Model	RE-150		
TECHNICAL DATA			
Working Temperature [°C]	[Water Bath] RT~99°C;±0.2°C [Oil Bath] RT~180°C; ±0.2°C		
Working Pressure [pa]	<399Pa[3mmHg]		
Environment Temperature [°C]	5~35°C		
Optimum Ambient Humidity	≤65%		
Glass Material	High Borosilicate Glass		
Lift Method	Manual		
ELECTRICAL REQUIREMENT	TE ELFR		
Voltage [V]	220		
Phase [P]	1 3		
Frequency [HZ]	50/60		
Total Power [W]	6200 9200		

ROTARY FLASK		
Volume [L]	50	
Sealing	PTFE	
Neck Interface[mm]	OD125 Flange	
BATH		
Bath Material	SUS304	
Bath Dimension [mm]	Ø560×300	
Volume [L]	74	
COLLECTION FLASK		
Volume [L]	20	
CONDENSER		
Туре	Vertical Up-Down Main-Auxiliary Condensers	
Condension Area [m^2]	2	
AGITATION & HEATING		
Motor Power [W]	200	
Rotation Speed [rpm]	20~110	
Heating Power [Kw]	6 [Single Phase] 9 [3 Phase]	
WEIGHT DIMENSION		
Unit Weight [Kg]	175	
Installation Dimension [mm]	1250×750×2100	

Package Information:

Length (cm)	Width (cm)	
Height (cm)	CBM (m3)	
Weight (kg)	Total capacity	
Product Serial No. 9097	2023-06-02 10:35:54	

Technical details and dimensions are subject to change. No liability is accepted for errors or omissions. Illustrations can deviate from the original.