

RE-505

Rotary evaporator is a common solvent recvery equipment in laboratory and production for chemistry, chemical industry, biology, medicine and other fields.

Lab1st RE-5 series is a rotary evaporator with motor lifting bath, which is easy to operate, economical and practical. It also consists of motor, roatary flask, motor lifting bath, condenser and other related parts. We provide standard rotovap from 1 liter to 100 liters, and larger volumes can be customized.



Rotary Evaporator, Motor Lift

Features:

Effective Rotavapor for limited budgets

Intuitive and easy operation at the highest safety level

High quality material guarantees a long lasting operation and protect your substance

All material is corrosion resistance and long lifespan, maintaining vecuum height.

Powerful, high-temperature heating bath, reaching 90°C [water bath] / 180°C [oil bath]

Turnkey solution is available, including chiller, vacuum pump and related accessories

Technical Data:

Model	RE-505		
TECHNICAL DATA			
Working Temperature [°C]	[Water Bath] RT~99°C;±0.2°C [Oil Bath] RT~180°C;±0.2°C		
Working Pressure [pa]	< 399Pa[3mmHg]		
Environment Temperature [°C]	5~35°C		
Optimum Ambient Humidity	≤65%		
Glass Material	High Borosilicate Glass		
Lift Method	Motor Lift		
ELECTRICAL REQUIREMENT	The surger // //		
Voltage [V]	220		
Phase [P]	1		
Frequency [HZ]	50/60		
Total Power [W]	2040		

ROTARY FLASK	
Volume [L]	5
Sealing	PTFE
Neck Interface [mm]	OD80 Flange
BATH	
Bath Material	SUS304
Bath Dimension [mm]	Ø280×170
Volume [L]	10
COLLECTION FLASK	
Volume [L]	3
Interface[mm]	OD50 Flange
CONDENSER	
Туре	Vertical Single Condenser
Condension Area [m^2]	0.5
Vacuum Port	OD10 Barb
Comdenser Port	OD16 Barb
AGITATION & HEATING	
Motor Power [W]	40
Rotation Speed [rpm]	10~140
Heating Power [Kw]	2
WEIGHT DIMENSION	
Unit Weight [Kg]	46
Installation Dimension [mm]	800×450×1090

Package Information:

Length (cm)	Width (cm)	
Height (cm)	CBM (m3)	
Weight (kg)	Total capacity	

Product Serial No. 9075

2023-06-02 11:07:13

Technical details and dimensions are subject to change. No liability is accepted for errors or omissions. Illustrations can deviate from the original.